

TOOL FEATURES

1. Robust gravity-casted engine pneumatic piston return design.
2. Hardened clinch teeth for clinch consistency & tool longevity.
3. Ergonomic rubber handle grip.
 - All metal construction.
 - Pneumatic piston return minimizes cycle time.
 - 3 nose lengths available.
 - Adjustable for left or right handed operation.



HR7
25mm (1")

HR7E
40mm (1.6")

HR77XE
70mm (2.8")



FASTENER SPECS

Type	15 GA. Bostitch RING15 / Meihotech GDH
Loading Capacity	100 Rings
Ring Height	12mm (1/2")
Crown Width	23.9mm (15/16")
Wire Dia.	1.8mm (0.07")
Open Ring Size	19mm (3/4")
Closure Ring Size	7.9~10.7mm (5/16"~27/64")

TOOL SPECS

Weight	HR7 : 1.39 kgs (3.0 lbs)
	HR7E : 1.53 kgs (3.4 lbs)
	HR77XE : 1.72 kgs (3.8 lbs)
Height	189mm (7.4")
Width	89mm (3.5")
Length	HR7 : 335mm (13.2")
	HR7E : 354mm (13.9")
	HR77XE : 381mm (15")
Operating Pressure	5.9~7.9 bar (85~115 psi)
Applications	Bag Closure, Bedding, Automotive Seating, Wire Cages, Fencing

